

## IMPORT 125 Lb. Cast Threaded Fittings

| Cat. No              | Description             | 1/8"<br>1/4" 3/8" | 1/2'  | 3/4'  | 1'    | 1 1/4' | 1 1/2' | 2"     | 2 1/2" | 3"     | 4"     | 5" | 6" |
|----------------------|-------------------------|-------------------|-------|-------|-------|--------|--------|--------|--------|--------|--------|----|----|
| <b>Elbows</b>        |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-235               | 90°                     | 4.13              | 6.29  | 8.46  | 13.05 | 20.76  | 25.92  | 42.20  | 82.79  | 126.98 | 306.24 |    |    |
| 62-235               | 90° RED                 | 6.40              | 6.80  | 9.26  | 16.25 | 25.38  | 32.06  | 59.16  | 100.24 | 160.11 | 361.98 |    |    |
| 62-290               | 45°                     | 4.53              | 5.75  | 8.46  | 14.29 | 22.85  | 28.63  | 46.42  | 90.93  | 146.17 | 334.15 |    |    |
| 62-254               | 90° Street              | 6.29              | 7.81  | 11.02 | 18.23 | 27.91  | 36.36  | 61.65  | 97.46  | 146.17 | 438.57 |    |    |
| 62-295               | 45° Street              | 6.40              | 7.81  | 11.02 | 18.23 | 27.91  | 37.48  | 63.53  |        |        |        |    |    |
| <b>Tees</b>          |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-460               | Straight                | 5.75              | 7.23  | 10.40 | 18.48 | 25.92  | 35.66  | 58.43  | 113.62 | 173.74 | 417.55 |    |    |
| 62-460               | Red 1 Opening           | 7.09              | 8.77  | 12.46 | 22.77 | 32.06  | 44.16  | 72.17  | 139.21 | 215.79 | 501.10 |    |    |
| 62-460               | Red 2 Openings          |                   |       | 13.70 | 24.80 | 34.79  |        |        |        |        |        |    |    |
| <b>Crosses</b>       |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-195               | Straight                | 9.60              | 11.67 | 16.86 | 26.73 | 41.84  | 53.46  | 111.41 | 208.75 |        |        |    |    |
| <b>Couplings</b>     |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-165               | Straight                | 4.13              | 5.19  | 6.85  | 10.40 | 16.25  | 22.09  | 36.36  | 60.19  | 83.52  | 160.11 |    |    |
| 62-165               | Red 1 or 2 Sizes        | 4.43              | 5.53  | 8.23  | 13.69 | 22.09  | 27.91  | 41.48  | 73.47  | 97.39  | 208.75 |    |    |
| 62-165               | Red more than 2 Sizes   |                   | 6.40  | 9.14  | 15.43 | 26.22  | 31.43  | 46.74  |        | 107.23 |        |    |    |
| <b>Bushings</b>      |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-144               | Hex Red 1 or 2 Sizes    | 3.04              | 3.28  | 4.53  | 6.85  | 11.67  | 14.91  | 22.09  | 44.17  | 66.80  | 153.19 |    |    |
| 62-144               | Hex Red 3 or more Sizes |                   | 3.91  | 5.46  | 8.31  | 14.08  | 18.23  | 26.61  | 54.80  | 86.84  | 180.99 |    |    |
| <b>Caps</b>          |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-155               |                         | 3.10              | 4.13  | 5.46  | 8.55  | 13.02  | 17.57  | 29.82  | 56.80  | 90.55  | 174.08 |    |    |
| <b>Plugs</b>         |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-396               | Regular                 |                   | 4.33  | 4.95  | 6.53  | 9.71   | 12.38  | 19.54  | 33.44  | 53.46  | 104.42 |    |    |
| 62-399               | Solid                   | 2.74              | 5.19  | 6.78  | 11.54 | 20.80  | 27.03  | 42.85  | 88.29  | 142.04 | 267.15 |    |    |
| <b>Locknuts</b>      |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-375               |                         | 2.05              | 3.28  | 3.91  | 5.83  | 9.50   | 12.31  | 19.56  | 33.44  | 53.46  | 104.42 |    |    |
| <b>Floor Flanges</b> |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-355               |                         |                   | 11.71 | 16.00 | 26.22 | 29.96  | 41.82  | 55.73  |        |        |        |    |    |
| <b>Unions</b>        |                         |                   |       |       |       |        |        |        |        |        |        |    |    |
| 62-657               |                         | 14.66             | 15.94 | 22.09 | 29.26 | 42.85  | 50.58  | 77.85  | 153.19 | 236.67 | 522.04 |    |    |

## Companion Flanges - Standard

| Cat. No                  | Description         | 1/2'          | 3/4'          | 1'            | 1 1/4'        | 1 1/2'    | 2"        | 2 1/2"    | 3"            | 4"        | 5"         | 6"         |
|--------------------------|---------------------|---------------|---------------|---------------|---------------|-----------|-----------|-----------|---------------|-----------|------------|------------|
| <b>Companion Flanges</b> | <b>150 lb. O.D.</b> | <b>3 1/2"</b> | <b>3 7/8"</b> | <b>4 1/4"</b> | <b>4 3/8"</b> | <b>5"</b> | <b>6"</b> | <b>7"</b> | <b>7 1/2"</b> | <b>9"</b> | <b>10"</b> | <b>11"</b> |
| 62-342                   |                     | 37.85         | 50.64         | 66.80         | 94.63         | 109.15    | 175.92    | 256.42    | 316.86        | 478.54    |            |            |

\*Consult Factory for minimum ordering quantities and pricing